

Betore Starting Work.

## **WORK AREA** Before Starting Work

- there is a danger of explosion. It will ignite Do not use this wailpaper stripper where
- DO NOT USE THIS EQUIPMENT ON CENINGS OF TOP ·7 tumes from petrol, or gas cylinder.
- plate would scald your face or hands. overhead work - the drips form the steam
- and that no-one is near to you or could Make sure that the area is clear and safe 3
- well clear. distract you. Keep children and animals
- others to keep away. Put up warning signs. Protect other people from the steam. Warn
- .9 is very suppery. Keep your work area clean; wet wallpaper ·G
- carpets, furnishings and floors. Move or protect furniture, hot water dripping from the steam plate will damage
- Do not stand the boiler unit on decorative
- place it on a neat resistant drip tray. drips of hot water may cause damage floors or other finish surfaces, the heat or
- ventilation and remove excessive moisture. Open doors or windows to improve

Frank Key. PLANT & Key. TOOL HIRE

v.112016

- environments may require a higher level of should be worn wherever you use this equipment. Particular jobs or edulpment (ppe) are the minimum that The following items of personal protective **SROTARAGO**
- brotection.
- You should wear heavy-duty waterproof ·7

- nose and plate. It anything is tound Check your equipment, cables, plugs steam **ЯЗЧЧІЯТС ЯЗЧАЧІЛА**
- contact the hire company. damaged, do not use the wallpaper stripper:

- noo sinegen uce vesociation ⊨urope





.8

.,

.9

.s

company.

are tight.

temporary or permanent disability must seek expert advice before using it.

v.hae.org.u

0901 Safety Guidance

It is important to read all of this leaflet

**BEFORE you use the Wallpaper Stripper** 

Plan your work and think ahead to make sure you will always

Electricity is dangerous and must always be used with great

Electricity and water make a hazardous combination. Keep

some straightforward work before starting on the main task.

waterproof gloves; Rcd if using a 230 volt (mains) supply.

electrical parts away from rain and water.

Steam will scaled or burn instantly; take great care.

Wallpaper Stripper

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

This wallpaper stripper is designed to remove all types of wallpaper, including emulsioned

The action of this wallpaper stripper can cause injury or damage if the equipment is no used

If you have not used a wallpaper stripper before, familiarise yourself with the equipment on

You should have at least the following items of personal protective equipment: Heavy duty

This equipment must not be used by minors, or by anyone under the influence of drugs or

This wallpaper stripper is designed for operation by an able bodied adult. Anyone with either

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins





you must know how to stop it.

Retore you switch the w

nujeze λont yands are dry.

protective glove or cloth.

or a blue industrial plug.

eavier than you think.

connections or improvise them.































Check on how the on/off switch operates

Do not touch electrical switches or plugs

allowing pressure to release slowly. Use a

and allow to cool then remove cap caretully

the turk offersting and hot. Shut off

Do not remove the filler cap while the

nuiess specifically recommended by the hire

Fill the tank up to the level mark with clean

Before starting, ensure all hose connections

designed to run directly from 230v mains will have either a normal square pin plug fitted,

has been supplied, rake care not to injure yourself when moving it about it may be

mains 230v supply. If a portable transformer

to power the equipment from a normal

plug fitted is designed to run off a special 10v supply. The hire company will have

Equipment with a cylindrical yellow industrial

matches your supply. Do not try to force

Check that the plug on your equipment

provided a portable transformer if you nee

vater only. Additives should not be used

















subaper stripper on,

tnemqiup3

to have arisen t

1.

3.

4.

5.

6.

7.

8

9

10.

alcoho

care

be working safely.

or washable paper

in a careful and controlled way.



əuı

44 (0) 121 333 4109

company. If the hire company have not given

any special instructions given by the hire

2. If you need to use an extension cable, follow

**Bnjd** 1. If you are using a portable

pin plug fitted or a blue industrial plug. Read the

230v equipment will have either a normal square

Your equipment will only operate on one voltage:

Do not use the steam plate near electrical

from the steam plate into it regularly. Do not

fill with water from the steam. Keep a bucket or container handy and empty the water

During use the steam concentrator plate will

Use a heat resistant drip tray where you can

concentrator plate will splutter hot water from the steam holes. Keep the steam plate

steam

As the water heats up the

230v extension cables.

transformer,

it will be 100v or 230v.

**ELECTRICAL SAFETY** 

sockets of switches.

use this water again.

away trom you.

**TAAM PLATE** 

ntted.

·7

230volt socket. Do not use any

transformer directly into the

110 VOLT HEATERS (YELLOW PLUG)

ιυειτησιιους ρειον τοι γουτ equipment.

e.org.uk

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

## Using the Wallpaper Stripper

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

1

1. Wear your gloves

Hæ

- 2. Each section of wallpaper treated will be very hot. Take care while handling it.
- 3. Switch off and remove the plug then allow the equipment to cool down completely before refilling.
- Always place the boiler unit on a heat resistant drip tray and not on a decorative 4. surface. Make sure the steam plate is placed on a heat resistant drip tray when not in use.
- 5. The part that stays hot longest is the filler cap. Allow it to cool then remove it carefully with a protective glove or cloth. Remove it in stages, allowing any pressure to release slowly.
- 6. Keep the cable clear of any sharp edges in your work area.
- 7. If you think the cable may be cut or damaged in any way, switch off and unplug at the mains before inspecting it. If the cable attached to the wallpaper stripper is damaged, stop using the equipment. Contact the hire company. If an extension cable has been damaged, do not use it again.
- Take care not to accidentally pull the plug from the socket. 8.
- Switch off and remove the plug from the socket then allow the equipment to cool 9. down before leaving unattended.
- 10. Switch off and remove the plug then allow the equipment to cool down completely before emptying.
- 11. If your equipment does not work properly do not attempt to repair it. Contact the hire company.
- 12. You may want to read this leaflet again. Please keep it until you finish work.
- Please keep this leaflet safely as it may be required for future reference













are dry and sate.

5. Make

catch fire.

ne rca.

damaged.

xteusiou cable con

sure

will overneat and could

run over it. Unroll it fully or it

suλ that

be trapped, and places where vehicles might

ασθες, ασοινιαλς οι ωπασως ψηέτε π. πισπ

than 50 metres (160 feet). Plug it directly into

a suitably rated heavy duty one, not longer

any special instructions, you should only use

company. If the hire company have not given

special instructions given by the hire

3. If you need an extension cable, tollow any

2. Use the "TEST" button to check that the rcd is

sable or equipment get

against electric shock if the

will help to protect you

equipment into the rcd. This

(золяве рім ов вгле ргле)

connections are dry and sate.

will overheat and could catch fire.

**SHATAAH TLOV 05S** 

according to the instructions supplied with it.

working each time you use it. Heset the roa

alrectly in to the 230 voit socket. Plug your

1. Use a residual current device ("rcd") plugged

4. Make sure that any extension cable

vehicles might run over it. Unroll it fully or it

where it might be trapped, and places where

idnige, sharp edges, doorways or windows

3. Lay the extension cable out carefully avoiding

between the transformer and the equipment.

You must only use an extension caple

cable, not longer than 50 metres (160 feet).

any special instructions, you should only use a suitably rated heavy duty 110v extension

4. Lay it out carefully avoiding liquids, sharp

5















