



# Using the Roughcast Applicator

1. Wear your protective equipment including dustmask and goggles.
2. The area must be clear as you need to get to large areas of the surface to be covered quickly.
3. If you need to work at height you must have a sturdy, safe platform that gives access to large areas of the surface. Do not try to work off ladders, it is unsafe and impractical.
4. You should carefully mask off window frames, doorframes and other areas where you do not want the cement mix to cover.
5. Practice on a hidden surface until you can confidently use the machine to get the result you want.
6. Use both hands to operate the applicator.
7. You should operate the applicator about 20cm to 25cm (8" to 10") from the surface. Keep the applicator moving while you crank the handle, do not let the mix build up at any one part of the surface.
8. Wash spots of cement mix off your skin immediately. Do not let it dry, do not just brush it off.
9. Clean up any stray bits of cement mix before they harden.
10. You must clean the applicator as soon as you have finished work before the mix goes hard.
11. Return the equipment to the hire shop in a clean condition.
12. If your equipment does not work properly do not attempt to repair it. Contact the hire company.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Solihull B37 7YE

Telephone: 44 (0) 121 380 4600  
Fax: 44 (0) 121 333 4109  
Email: mail@hae.org.uk  
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

## It is important to read all of this leaflet BEFORE using the Roughcast Applicator



1. Plan your work and think ahead to make sure you will always be working safely.
2. Cement mixes are harmful to eyes, lungs and skin. Follow any instructions given by the manufacturers of these cement products.
3. This roughcast applicator is designed for the application of a Tyrolean type cement finish to external and internal walls. It will also apply plaster and proprietary paint mixes as a decorative finish.
4. The action of this equipment can cause injury or damage if the equipment is not used in a careful and controlled way.
5. If you have not used a roughcast applicator before, familiarise yourself with how the equipment works before you start on the main task.
6. You must have at least the following items of personal protective equipment:  
Goggles: EN166 or BS2092;  
Dust mask – a minimum of EN149 FFP3(s) protection;  
Overalls with long sleeves and full trousers;  
Gloves
7. This equipment must not be used by minors, or by anyone under the influence of drugs or alcohol.
8. This roughcast applicator is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Solihull B37 7YE



1. Make sure that the area is clear and safe and that no-one is near to you or could distract you.
2. Protect other people from the spray. Warn others to keep away, put barriers around your work area.
3. You need easy access to any part of the surface to be covered, so make sure that you have a safe and secure platform if you plan to work over shoulder height.
1. The following items of personal protective equipment (ppe) are the minimum that should be worn whenever you use this mixer. Particular jobs or environments may require a higher level of protection.
2. You must wear goggles (EN166 or BS2092) when you are working with this equipment.
3. You will need to wear an appropriate dustmask (with a minimum of EN149:2001 FFP3 protection) when you are mixing materials that cause dust or spray.
4. You should wear gloves, long sleeves and full trousers to prevent the mixes coming into contact with your bare skin.
5. Anybody who is working near to you will also need to wear appropriate personal protective equipment.

### ROUGHCAST APPLICATOR



### OPERATORS



### CEMENT MIXES AND CONTACT DERMATITIS

1. Wet cement mix is one of several substances that can cause contact dermatitis.

### WORK AREA

2. Contact dermatitis is a rash that may occur when the skin reacts to certain substances. The rash can vary but it is usually itchy and causes flaky skin. The rash occurs only where the substance was in contact with the skin.
3. Wash cement or plaster mixes off your skin immediately. Thoroughly rinse out your eyes and seek medical advice if you get any type of cement mix in them.
4. Mild dermatitis will heal providing there is no further contact. If the rash persists seek medical advice.

v:032017