



For guidance on managing construction health risks go to www.hse.gov.uk/construction





- · Rungs Free from damage
- Castings No cracks

FRAMES & LADDERS

- Weld Free from cracks
- Uprights/tubes Straight
- Reinforcements
- Clip-in guard rail/Hand rail frames
- Ladder/Stiles/Rungs Free from

DECKS/PLATFORMS

- Hooks -Function freely
- Supports
- Welds Free from cracks
- Deck fixing rivets
- Deck damage
- Hinges Function
- Labels States SWL

TOE BOARDS AND CLIPS

- Timber Straight
- Fittings Function

CASTOR AND ADJUSTABLE LEGS

- Adjusters Moves freely
- Thread Free from damage
- End Collar Free from damage
- Wheels Move & Rotate
- Spindle
- Brake Check function
- Housing
- Spigot

OUTRIGGERS OR STABILISERS

- Castings Free from damage
- Tubes Straight & free from dents
- Foot
- Nuts & Bolts
- Interlock Clips Function
- Welds Free from cracks
- Clip function

Please keep this leaflet safely as it may be required for future reference









2450 Regents Court The Crescent









©Copyright Hire Association Europe April 2011

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited













naing the simple check guide on the luspect the components before use

SETTING UP

reverse of this leafiel.

uiuded openings, these remain closed 3. Ensure that where platforms have

removed. In most circumstances these əа circumstances must these decks/platforms. ∩uder working gll rails/hand rails and toe boards are in 2. Ensure that the required guard

methods. Seek advice from your "tied-in" using approved necessary for the mobile access tower 7. Under certain conditions it may be

USING THE MOBILE ACCESS TOWER

height of the tower and re-erect it at the conditions, uneven ground or slight wind, it may be safer to reduce the

position while standing on the ground. mobile access tower to its new been removed. Push and pull the nun sii bersons and equipment nas Do not move the mobile access tower

the side of a building or other rigid the tower by pushing too hard against on the platform, take care not to topple When drilling or using other equipment

.meni they will act like a sail if the wind catches sheeting and tarpaulins on the tower: outside if it is windy. Take care using Do not use the mobile access tower

manufacturers assembly guide. interior or exterior use in assembled to the heights specified for The mobile tower must only be

plates and appropriate load bearing castors should be replaced with base need on soft or uneven ground, suitable. Where the equipment may be tower make sure the ground surface is Before setting up the mobile access

ssemble guide. the manufacturers unuper of components are used as 1. Ensure that the correct type and

MOBILE ACCESS TOWER SYSTEMS











Mobile Access Towers

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

Important note: This document must be read in conjunction with the original assembly quide

1201 Safety Guidance

- 1. It is important to read this leaflet and the manufactures assembly guide before you use the mobile access tower
- Do not exceed the maximum load of the mobile access tower. This information is detailed on the castors of the
- Do not exceed the Safe Working Load (SWL) detailed on each of the working platforms/Decks. If you have not used assembled or dismantled a mobile access tower before
- familiarise yourself with the equipment's components before you start the main task.
- Plan your work and think ahead to make sure that you will always be working safely.
- Prepare a risk assessment for the task.
- You should have at least the following items of personal protective equipment:
 - Hard hat with chin strap to EN397
 - Boots or protective footwear to a minimum EN345
- The mobile access tower must not be used by minors, or by anyone under the influence of drugs or alcohol.
- This equipment is designed for use by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.
- If the mobile access tower is to remain in position when unattended, for example overnight, then you should make it secure to prevent unauthorised use.















Frank Key. PLANT & Key. TOOL HIRE

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia mort has been made by That/ETA to ensure that the minimation great in this document and support is accurate and not misleading. HAE/ETA cannot accept responsibility for any loss or liability so proposed and the minimation of the support of the support is a support of the supp to have arisen from the use of any such document/material. Only Acts of Parliament and Statu.
have the force of law and only the courts can authoritatively interpret the law.

44 (0) 121 380 4600 44 (0) 121 333 4109

BAY 788 Iludilos The Crescent Birmingham Business Park noo sinegen uch



will also need to wear appropriate Persons working near this equipment Hard hat with chin strap to EN397.

footwear ideally safety boots to EN345. You must wear suitable protective whenever using mobile access towers.

bersonal protective equipment.

minimum that should be worn biotective equipment (ppe) are the 1. The following items of personal

LOWER DISMANTLING MOBILE ACCESS PERONS USING/ASSEMBLING OR

from other services. where possible isolate potential risks Keep away from electrical services and

inspected for hidden underground surfaces. Ensure that the ground is 4. Use with caution on uneven or sloping

local government. authority may be required from the pedestrian areas, a permit or written In certain locations, such as public and

barriers and signs around your work Warn others to keep away, place associated with working at height. Protect other people from the risk

conia distract you. safe and that no one is near to you or Make sure that the area is clear and

WORK AREA

company or the insurer straight away. insurance cover, check with the nire 2. If you are in doubt about your

HONAHUSNI

will give you any protection. nulikely that a normal insurance policy плогиед пл а підпиау ассіделі, ії із belonging to a third party, or if you are you cause any damage to property 4. In addition, you should be aware that if

Please keep it until you finish work .

You may want to read this leaflet again.

eduipment yourself against theft or 3. However, you must always secure the

2. Some hire companies will offer vandalism.

unreasonable damage such company SSOI รูปลเทรเ equipment. You must indemnify the responsible for the safe custody of the 1. Under the terms of hire, you are



are a mandatory requirement.

anbbuer

new location. 7. If moving the tower in adverse









