



1301 Safety Guidance

It is important to read all of this leaflet

BEFORE you use the Site Fan

always be working safely.

with great care.

Plan your work and think ahead to make sure you will

Electricity can be hazardous and must always be used

This fan is designed to circulate the air within a building

producing a stream of cool air to reduce the temperature.

and the precautions you should take before you start to use it.

Site Fan

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

This fan can cause injury or damage if it is not used in a careful and controlled way. If you have not used a fan before, familiarise yourself with the potential hazards

You should use a residual current device 'rcd' to help protect you against electric

This fan must not be used by minors, or by anyone under the influence of drugs

This fan is designed for use by an able bodied adult. Anyone with either temporary or



Using the Site Fan

- Use an rcd if your fan uses a 230 volt supply
- Make sure the fan is sited in a safe secure place before switching on.
- Do not move the fan while it is running.
- Do not allow anyone to stand in front of the fan, the dust particles blown up by the fan could be dangerous to health especially if blown into the eye.
- This fan can also be used to improve the ventilation of a building.
- Switch off and unplug, before moving the fan. 6.
- Switch off and unplug if you are not using the fan.
- If you think the cable may be cut or damaged in any way, switch off and unplug at the mains before inspecting it. If the cable attached to the fan is damaged, stop using the fan. Contact the hire company. If an extension cable has been damaged, do not use it again.

Please keep this leaflet safely as it may be required for future reference



- Take care not to accidentally pull the plug from the socket.
- 10. If your equipment does not work properly, do not attempt to repair it. Contact the hire company.





connections are dry and sare.

could catch fire.

5. Make sure that any extension cable

Unroll it fully or it will overheat and

where vehicles might run over it.

where it might be trapped, and places

sharp edges, doorways or windows

longer than 50 metres (160 feet).

suitably rated heavy duty one, not

instructions, you should only use a

sbecial

it. Reset the rcd according to the

eh rcd is working each time you use

you against electric shock if the cable

into the rcd. This will help to protect

2. Use the 'TEST' button to check that

any special

4. Lay it out carefully avoiding liquids,

Plug it directly into the rcd.

have not given

the hire company

the hire company. If

instructions given by

extension cable, follow

instructions supplied with it.

If you need

or fan get damaged.

socket. Plug your fan

directly into the 230 volt

device ('rcd') plugged

1. Use a residual current

suλ













shock if using a 230 volt (mains) supply.



to have arisen from the use of any such document/material. Only Acts of Parliament and Statu.

have the force of law and only the courts can authoritatively interpret the law.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability percurates are accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability percurates are accurate and some accurate and statutory institutions.

permanent disability must seek expert advice before using it.









2450 Regents Court The Crescent

44 (0) 121 333 4109

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

44 (0) 121 380 4600 44 (0) 121 333 4109

BAY 788 Iludilos The Crescent Birmingham Business Park nuo sinagan uah



connections are dry and sate.

catch fire. rully or it will overneat and could vehicles might run over it. Unroll it pe frapped, and places where doorways or windows where it might avoiding liquids, sharp edges 3. Lay the extension cable out carefully

4. Make sure that any extension cable

transformer and the lan. nse an extension cable between the 50 metres (160 teet). You must only 100v extension cable, not longer than only use a suitably rated heavy duty any special instructions, you should company have not given

hire company. If the hire instructions given by the suy special WOIIOI z. If you need to use an extension cable,

directly into the 230 volt socket. Do 1. If you are using a portable transformer, plug the transformer

110 VOLT HEATERS (YELLOW PLUG)

below for your fan.

a yellow industrial plug fitted, or a blue If will be 100v or 230v. 110v tans will have Your fan will only operate on one voltage: **ELECTRICAL SAFETY**

on, you must know how to switch it oberates - before you switch the fan Check on how the on/off switch

only, do not use it outside. This fan is for use inside buildings

through th grille while the fan is

Do not push fingers or anything else and outlets while the fan is in use.

Do not cover or block the air intakes

titted, or a blue industrial plug. either a normal square pin plug directly from 230v mains will have than you think. Fans designed to run moving it about - it may be heavier care not to injure yourself when transformer has been supplied, take 230v supply. It a portable power the fan from a normal mains

portable transformer if you need to hire company will have provided a run off a special 100v supply. The industrial plug fitted are designed to Eans with a cylindrical yellow

torce connections or improvise them. matches your supply. Do not try to Check that the plug on your fan

- confact the hire company. damaged, do not use the equipment equipment. If anything is found Check your fan, cable and plug and

where it might get wet. Do not use this fan in the rain or

it has been set up sately. 4. This fan can be left unattended once

airliow to touch the tan while it is in not allow anyone to stand in the flying debris blown by the fan. Do Protect other people form possible

optimize its efficiency. from walls and other obstructions to SIG ruis ran in a sare prace away

fumes from petrol, or gas cylinders.

danger of explosion. It will ignite 1. Do not use this fan where there is a

MORK AREA Before Starting Work



not use any 230v extension cables.

Read the instructions industrial plug.















(SQUARE PIN OR BLUE PLUG) 230 VOLI HEATERS